

iCombi Classic overview of models.

Classic features, multiple possibilities.



The iCombi Classic is available in many different sizes, as ultimately its performance fits your needs and not the other way round. 20 meals or 2,000? Front of house cooking? Size of kitchen? Electricity? Gas? 6-1/1? 20-2/1? Which model belongs in your kitchen?

All the options, equipment features and accessories at: rational-online.com

iCombi Classic	6-1/1	10-1/1	6-2/1	10-2/1	20-1/1	20-2/1
Electric and gas						
Capacity	6 × 1/1 GN	10 × 1/1 GN	6 × 2/1 GN	10 × 2/1 GN	20 × 1/1 GN	20 × 2/1 GN
Number of meals per day	30–100	80–150	60–160	150–300	150–300	300–500
Lengthwise loading (GN)	1/1, 1/2, 2/3, 1/3, 2/8 GN	1/1, 1/2, 2/3, 1/3, 2/8 GN	2/1, 1/1 GN	2/1, 1/1 GN	1/1, 1/2, 2/3, 1/3, 2/8 GN	2/1, 1/1 GN
Width	850 mm	850 mm	1072 mm	1072 mm	877 mm	1082 mm
Depth (including door handle)	842 mm	842 mm	1042 mm	1042 mm	913 mm	1117 mm
Height	754 mm	1014 mm	754 mm	1014 mm	1807 mm	1807 mm
Water inlet	R 3/4"	R 3/4"	R 3/4"	R 3/4"	R 3/4"	R 3/4"
Water outlet	DN 50	DN 50	DN 50	DN 50	DN 50	DN 50
Water pressure	1,0 - 6,0 bar	1,0 - 6,0 bar	1,0 - 6,0 bar	1,0 - 6,0 bar	1,0 - 6,0 bar	1,0 - 6,0 bar
Electric						
Weight	93 kg	121 kg	131 kg	160 kg	231 kg	304 kg
Connected load	10.8 kW	18.9 kW	22.4 kW	37.4 kW	37.2 kW	67.9 kW
Fuse	3 × 16 A	3 × 32 A	3 × 35 A	3 × 63 A	3 × 63 A	3 × 100 A
Main connections**	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V
Convection mode output	10.25 kW	18 kW	21.6 kW	36 kW	36 kW	66 kW
Steam mode output	9 kW	18 kW	18 kW	36 kW	36 kW	54 kW
Gas						
Weight	101 kg	139 kg	128 kg	184 kg	276 kg	371 kg
Electrical rating	0.6 kW	0.9 kW	0.9 kW	1.5 kW	1.3 kW	2.2 kW
Fuse	1 × 16 A	1 × 16 A	1 × 16 A	1 × 16 A	1 × 16 A	1 × 16 A
Mains connection	1 NAC 230 V	1 NAC 230 V	1 NAC 230 V	1 NAC 230 V	1 NAC 230 V	1 NAC 230 V
Gas supply/connection	3/4" IG	3/4" IG	3/4" IG	3/4" IG	3/4" IG	3/4" IG
Natural gas/ Liquid gas LPG G30*						
Max. Nominal thermal load	13 kW/13.5 kW	22 kW/23 kW	28 kW/29.5 kW	40 kW/42 kW	42 kW/44 kW	80 kW/84 kW
Convection mode output	13 kW/13.5 kW	22 kW/23 kW	28 kW/29.5 kW	40 kW/42 kW	42 kW/44 kW	80 kW/84 kW
Steam mode output	12 kW/12.5 kW	20 kW/21 kW	21 kW/22 kW	40 kW/42 kW	38 kW/40 kW	51 kW/53.5 kW

* To guarantee proper operation, the appropriate connection flow pressure must be ensured:
Natural gas H G20: 18–25 mbar (0.261–0.363 psi), LPG G30: 25–57.5 mbar (0.363–0.834 psi).

** Other voltages and gas types are available upon request.

X5 and 20-2/1 Electric: ENERGY STAR excludes these unit features from certification.

