

iCombi Pro overview of models.

Which model is the right one for you?

The iCombi Pro is available in many different sizes, as ultimately its performance needs to fit your needs and not the other way around. 20 meals or 2,000? Front of house cooking? Size of kitchen? Electricity? Gas? XS? 20-2/1? Which model belongs in your kitchen?

All the options, equipment features and accessories at: rational-online.com



iCombi Classic – technology meets craftsmanship.
The iCombi Classic is robust, easy to use and works just as precisely as you. Therefore, it is the tailored solution for those who are experienced and want to operate their combi-steamer manually.



iVario Pro – Completely different, but still RATIONAL.
Boiling, frying, deep-frying the iVario Pro, which works with contact heat, is the ideal addition to the iCombi Pro. Intelligent, convenient, flexible. An unbeatable team.



iCombi Pro	XS 6-2/3	6-1/1	10-1/1	6-2/1	10-2/1	20-1/1	20-2/1
Electric and gas							
Capacity	6 × 2/3 GN	6 × 1/1 GN	10 × 1/1 GN	6 × 2/1 GN	10 × 2/1 GN	20 × 1/1 GN	20 × 2/1 GN
Number of meals per day	20–80	30–100	80–150	60–160	150–300	150–300	300–500
Lengthwise loading (GN)	1/2, 2/3, 1/3, 2/8 GN	1/1, 1/2, 2/3, 1/3, 2/8 GN	1/1, 1/2, 2/3, 1/3, 2/8 GN	2/1, 1/1 GN	2/1, 1/1 GN	1/1, 1/2, 2/3, 1/3, 2/8 GN	2/1, 1/1 GN
Width	655 mm	850 mm	850 mm	1072 mm	1072 mm	877 mm	1082 mm
Depth (including door handle)	621 mm	842 mm	842 mm	1042 mm	1042 mm	913 mm	1117 mm
Height	567 mm	754 mm	1014 mm	754 mm	1014 mm	1807 mm	1807 mm
Water inlet	R 3/4"	R 3/4"	R 3/4"	R 3/4"	R 3/4"	R 3/4"	R 3/4"
Water outlet	DN 40	DN 50	DN 50	DN 50	DN 50	DN 50	DN 50
Water pressure	1.0 – 6.0 bar	1.0 – 6.0 bar	1.0 – 6.0 bar	1.0 – 6.0 bar	1.0 – 6.0 bar	1.0 – 6.0 bar	1.0 – 6.0 bar
Electric							
Weight	67 kg	99 kg	127 kg	137 kg	179 kg	263 kg	336 kg
Connected load	5,7 kW	10,8 kW	18,9 kW	22,4 kW	37,4 kW	37,2 kW	67,9 kW
Fuse	3 × 10 A	3 × 16 A	3 × 32 A	3 × 35 A	3 × 63 A	3 × 63 A	3 × 100 A
Mains connection	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V
Convection mode output	5,4 kW	10,25 kW	18 kW	21,6 kW	36 kW	36 kW	66 kW
Steam mode output	5,4 kW	9 kW	18 kW	18 kW	36 kW	36 kW	54 kW
Gas							
Weight		117 kg	155 kg	144 kg	192 kg	284 kg	379 kg
Electrical rating		0,6 kW	0,9 kW	0,9 kW	1,5 kW	1,3 kW	2,2 kW
Fuse		1 × 16 A	1 × 16 A	1 × 16 A	1 × 16 A	1 × 16 A	1 × 16 A
Mains connection		1 NAC 230 V	1 NAC 230 V	1 NAC 230 V	1 NAC 230 V	1 NAC 230 V	1 NAC 230 V
Gas connection		3/4" IG	3/4" IG	3/4" IG	3/4" IG	3/4" IG	3/4" IG
Natural gas /LPG G31/LPG G30*							
Max. Nominal thermal load		13 kW/13 kW/ 13,5 kW	22 kW/22 kW/ 23 kW	28 kW/28 kW/ 29,5 kW	40 kW/40 kW/ 42 kW	42 kW/42 kW/ 44 kW	80 kW/80 kW/ 84 kW
Convection mode output		13 kW/13 kW/ 13,5 kW	22 kW/22 kW/ 23 kW	28 kW/28 kW/ 29,5 kW	40 kW/40 kW/ 42 kW	42 kW/42 kW/ 44 kW	80 kW/80 kW/ 84 kW
Steam mode output		12 kW/12 kW/ 12,5 kW	20 kW/20 kW/ 21 kW	21 kW/21 kW/ 22 kW	40 kW/40 kW/ 42 kW	38 kW/38 kW/ 40 kW	51 kW/51 kW/ 53,5 kW

* To guarantee proper operation, the appropriate connection flow pressure must be ensured:
Natural gas H G20 18–25 mbar (0.261–0.363 psi). Natural gas L G25: 20–30 mbar (0.290–0.435 psi). LPG G30 und G31: 25–57.5 mbar (0.363–0.834 psi).
XS and 20-2/1 Electric: ENERGY STAR excludes these unit features from certification.

